

Product data sheet

9007C52B2

Limit switch 9007C, 600 VAC, 10 A, option version

Main

Range of product	9007
Series name	Heavy duty
Product or component type	Limit switch
Device short name	9007C
Product specific application	Compact box
ETIM classification	ETIM 9 - EC000030 - End switch
Body type	Plug-in
Head type	Rotary head
Material	Metal
Body material	Zinc
Head material	Zinc
Fixing mode	By the body
Movement of operating head	Rotary
Type of operator	Zinc spring return without operating lever (-)9007C lever
Switch actuation	CW and CCW from left and right
Type of approach	Lateral approach, 1 or 2 programmable direction
Number of poles	1
Range compatibility	9007
Indivisible sale quantity	1
Sale per indivisible quantity	1

Complementary

Mechanical durability	10000000 cycles
Tripping angle	10 °
Maximum actuation speed	90 ft/min with 45° cam angle, levers only, 130 ft/min with 30° cam angle, levers only
Cable entry	1 entry for 1/2" - 14 NPT conforming to ANSI B1.20.1
Repeat accuracy	+/- 0.002 in linear travel of cam
Electrical durability	1000000 cycles
Electrical connection	Screw-clamp terminals (AWG 22...AWG 12), 1-2

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Positive opening	Without
Contact form	Form Z
Contacts type and composition	NC-NO
Contacts material	Silver contacts
Terminals description ISO n°1	(1-2)NC (3-4)NO
Contact operation	Snap action
[Uimp] rated impulse withstand voltage	2.5 kV AC 1 min conforming to CE, 2.2 kV AC 1 min conforming to UL, 2.64 kV AC 1 s conforming to CSA
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to UL 508 for contact block, 600 V (pollution degree 3) conforming to CSA C22.2 No 14 for contact block
[Ie] rated operational current	1.2 A at 600 V AC, A600 conforming to NEMA, 1.5 A at 480 V AC, A600 conforming to NEMA, 3 A at 240 V AC, A600 conforming to NEMA, 6 A at 120 V AC, A600 conforming to NEMA, 0.1 A at 600 V DC, Q600 conforming to NEMA, 0.27 A at 250 V AC, Q600 conforming to NEMA, 0.55 A at 125 V DC, Q600 conforming to NEMA
[Ithe] conventional enclosed thermal current	10 A
Electrical shock protection class	Class 0 conforming to IEC 61140
Short-circuit protection	10 A by CC fuse, protection type: non-time delay
Local signalling	without
Switch function	SPDT-DB
Function available	Not applicable
Width	1.55 in
Depth	2.5 in
Product weight	1.25 livre

Environment

Environmental characteristic	Standard environment
IP degree of protection	IP67 conforming to IEC 60529
NEMA degree of protection	NEMA 1 conforming to Nema type 250, NEMA 2 conforming to Nema type 250, NEMA 4 conforming to Nema type 250, NEMA 6 conforming to Nema type 250, NEMA 6P conforming to Nema type 250, NEMA 12 conforming to Nema type 250, NEMA 13 conforming to Nema type 250
Ambient air temperature for operation	-29…85 °C
Ambient air temperature for storage	-29…85 °C
Shock resistance	60 gn for 9 ms conforming to IEC 60068-2-27
Vibration resistance	25 gn (f= 10-150 Hz) conforming to IEC 60068-2-6
Protective treatment	Epoxy powder coat

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months

Packing Units

Country of origin	MX (Mexico)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916098592
Package 1 height	4.318 cm
Package 1 width	7.112 cm
Package 1 length	10.668 cm
Package 1 weight	0.481 kg
Unit type of package 2	CAR
Number of units in package 2	1
New Package 2 GTIN 14	13666916098599
Package 2 height	10.5 cm
Package 2 width	6.9 cm
Package 2 length	4.1 cm
Package 2 weight	0.567 kg
Unit type of package 3	PAL
Number of units in package 3	510
New Package 3 GTIN 14	23666916098596
Package 3 height	101.6 cm
Package 3 width	101.6 cm
Package 3 length	121.92 cm
Package 3 weight	245.393 kg