

Product data sheet

XCSL566B1

Safety interlock switch XCSL, metal, solenoid, 300 VAC, 10 A

Main

ETIM classification	ETIM 9 - EC002593 - Position switch with guard locking
Enclosure type	Water resistant enclosure for indoor/outdoor, dustproof enclosure for indoor/outdoor, ice/sleet proof enclosure for indoor/outdoor
Enclosure material	metal enclosure
Number of poles	3
Locking options description	With locking of actuator, unlocking by key operated lock
Product certifications	CE CSA LR4408794 class 3211 03 UL listed file E164353 CCN NKCR
Indivisible sale quantity	1

Complementary

Contact operation	Slow-break, break before make
[Us] rated supply voltage	24 V DC
Permissible voltage	300 V AC
[In] rated current	10 A
Depth	1.73 in

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-25…70 °C

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Country of origin	FR (France)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916008713
Package 1 height	5.2 cm
Package 1 width	6.2 cm
Package 1 length	28 cm
Package 1 weight	0.968 kg
Unit type of package 2	S02
Number of units in package 2	8
New Package 2 GTIN 14	13666916008710
Package 2 height	15 cm
Package 2 width	30 cm
Package 2 length	40 cm
Package 2 weight	8.199 kg
Unit type of package 3	CAR
Number of units in package 3	1
New Package 3 GTIN 14	23666916008717
Package 3 height	28 cm
Package 3 width	5.2 cm
Package 3 length	6.2 cm
Package 3 weight	0.968 kg