

Product data sheet

XCSP3919P20

Safety limit switch XCSP, plastic, 2NC+1NO, 1 entry tapped M20 x 1.5, rotary lever

Main

Range of product	Telemecanique Safety switches XCS
Product or component type	Safety limit switch
Component name	XCSP
Design	Compact
Sensor design	Compact
ETIM classification	ETIM 9 - EC000030 - End switch
Head type	Rotary head
Material	Plastic
Body material	Plastic
Head material	Zamak
Enclosure material	Plastic
Type of operator	Steel roller lever
Switch actuation	By 30° cam
Number of poles	3
Safety level	Can reach category 4 with the appropriate monitoring system and correctly wired conforming to ISO 13849-1, can reach PL = e with the appropriate monitoring system and correctly wired conforming to ISO 13849-1, can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to IEC 61508
Safety reliability data	B10d = 50000000 value given for a life time of 20 years limited by mechanical or contact wear
Protection technology	Plastic protective cover, secured by 5-lobe socket head safety screw
Product certifications	CSA UL
Standards	CSA C22.2 No 14 EN 1088/ISO 14119 IEC 60204-1 IEC 60947-5-1 UL 508
Indivisible sale quantity	1

Complementary

Mechanical durability	10000000 cycles
Minimum torque for tripping	0.1 N.m
Cable entry	1 entry tapped for M20 x 1.5

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contact code designation	B300, AC-15 (Ue = 240 V, Ie = 1.5 A) conforming to IEC 60947-5-1 appendix A, R300, DC-13 (Ue = 250 V, Ie = 0.1 A) conforming to IEC 60947-5-1 appendix A
Repeat accuracy	0.1 mm on tripping points, 1 million operating cycles for head with end plunger
Electrical connection	Terminal
Positive opening	With NC contact
Positive opening minimum torque	0.25 N.m
Contacts type and composition	1 NC + 1 NC + 1 NO
Contact operation	Snap action
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1, 4 kV conforming to IEC 60664
[Ui] rated insulation voltage	300 V conforming to UL 508, 400 V (pollution degree 3) conforming to IEC 60947-1, 300 V conforming to CSA C22.2 No 14
[Ithe] conventional enclosed thermal current	6 A
Resistance across terminals	25 MOhm conforming to IEC 60255-7 category 3
Electrical shock protection class	Class II
Short-circuit protection	6 A cartridge fuse type gG (gl)
Clamping connection capacity	1 x 0.34...2 x 0.75 mm²
Width	34 mm
Depth	35 mm
Product weight	0.22 kg

Environment

IK degree of protection	IK04 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529, IP67 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27
Vibration resistance	25 gn (f= 10-500 Hz) conforming to IEC 60068-2-6
Protective treatment	TC

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months

Packing Units

Country of origin	FR (France)

Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916045343
Package 1 height	13.3 cm
Package 1 width	3.3 cm
Package 1 length	5.1 cm
Package 1 weight	0.15 kg
Unit type of package 2	S01
Number of units in package 2	6
New Package 2 GTIN 14	13666916045340
Package 2 height	15 cm
Package 2 width	15 cm
Package 2 length	40 cm
Package 2 weight	1.104 kg
New Package 3 GTIN 14	23666916045347