

# Product data sheet

# XCSPR752

Safety switch XCSPR, 2NC, M16, hinge, spindle 30 mm

## Main

| | |
|---|---|
| Range of product | Telemecanique Safety switches XCS |
| Product or component type | Guard switch |
| Component name | XCSPR |
| ETIM classification | ETIM 9 - EC000030 - End switch |
| Head type | Turret head rotary axis |
| Material | Plastic |
| Lever material | Stainless steel |
| Enclosure material | Polyamide PA66 fibre glass impregnated |
| Type of operator | Spindle 30 mm |
| Number of poles | 2 |
| Safety level | Can reach category 4 with the appropriate monitoring system and correctly wired conforming to ISO 13849-1, can reach PL = e with the appropriate monitoring system and correctly wired conforming to ISO 13849-1, can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to IEC 61508 |
| Safety reliability data | B10d = 5000000 value given for a life time of 20 years limited by mechanical or contact wear |
| Product certifications | BG<br>CSA<br>UL |
| Standards | CSA C22.2 No 14<br>EN 1088/ISO 14119<br>IEC 60204-1<br>IEC 60947-5-1<br>IEC 60947-5-4<br>ISO 12100<br>UL 508 |
| Indivisible sale quantity | 1 |

## Complementary

| | |
|---|---|
| Mechanical durability | 1000000 cycles |
| Minimum torque for tripping | 0.1 N.m |
| Cable entry | 1 entry tapped for M16 x 1.5 |
| Contact code designation | A300, AC-15 (Ue = 120 V, Ie = 6 A) conforming to IEC 60947-5-1, A300, AC-15 (Ue = 240 V, Ie = 3 A) conforming to IEC 60947-5-1, Q300, DC-13 (Ue = 125 V, Ie = 0.55 A) conforming to IEC 60947-5-1, Q300, DC-13 (Ue = 250 V, Ie = 0.27 A) conforming to IEC 60947-5-1 |
| Electrical connection | Terminal |
| Positive opening | With NC contact |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| Positive opening minimum torque | 0.25 N.m |
| Contacts type and composition | 1 NC + 1 NC |
| Contact operation | Slow-break |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-5-1 |
| [Ui] rated insulation voltage | 300 V conforming to UL 508, 300 V conforming to CSA C22.2 No 14, 500 V (pollution degree 3) conforming to IEC 60947-1 |
| [Ithe] conventional enclosed thermal current | 10 A |
| Resistance across terminals | 30 mOhm conforming to IEC 60947-5-4 |
| Electrical shock protection class | Class II conforming to IEC 61140 |
| Short-circuit protection | 10 A cartridge fuse type gG (gI) |
| Insulation | Double insulated |
| Clamping connection capacity | 1 x 0.5...2 x 1.5 mm² with or without cable end |
| Width | 30 mm |
| Depth | 60 mm |
| Product weight | 0.105 kg |

## Environment

| | |
|---|---|
| IP degree of protection | IP67 conforming to IEC 60529 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |
| Shock resistance | 50 gn for 11 ms conforming to IEC 60068-2-27 |
| Vibration resistance | 50 gn (f= 10-500 Hz) conforming to IEC 60068-2-6 |
| Protective treatment | TC<br>TH |

## Offer Sustainability

| | |
|---|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Warranty

| | |
|---|---|
| Warranty | 18 months |

## Packing Units

| | |
|---|---|
| Country of origin | FR (France) |
| Unit type of package 1 | PCE |
| Number of units in package 1 | 1 |
| New Package 1 GTIN-13 | 3666916045893 |
| Package 1 height | 4 cm |

| | |
|---|---|
| Package 1 width | 11.5 cm |
| Package 1 length | 11.5 cm |
| Package 1 weight | 0.138 kg |
| Unit type of package 2 | S02 |
| Number of units in package 2 | 18 |
| New Package 2 GTIN 14 | 13666916045890 |
| Package 2 height | 15 cm |
| Package 2 width | 30 cm |
| Package 2 length | 40 cm |
| Package 2 weight | 2.78 kg |
| Unit type of package 3 | S03 |
| Number of units in package 3 | 50 |
| New Package 3 GTIN 14 | 23666916045897 |
| Package 3 height | 30 cm |
| Package 3 width | 30 cm |
| Package 3 length | 40 cm |