

Product data sheet

XCSTE7513

Safety interlock XCSTE, plastic, 2NC, slow break, 1 entry tapped 1/2" NPT

Main

Range of product	Telemecanique Safety switches XCS
Product or component type	Safety switch
Component name	XCSTE
Design	Rectangular
Sensor design	RECTANGULAR
ETIM classification	ETIM 9 - EC002593 - Position switch with guard locking
Head type	Key operated turret head
Material	Plastic
Body material	PA (polyamide)
Head material	PA (polyamide)
Number of poles	2
Safety level	Can reach category 4 with the appropriate monitoring system and correctly wired conforming to ISO 13849-1, can reach PL = e with the appropriate monitoring system and correctly wired conforming to ISO 13849-1, can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to IEC 61508
Safety reliability data	B10d = 5000000 value given for a life time of 20 years limited by mechanical or contact wear
Locking options description	With interlocking, locking by solenoid
Electromagnet interlocking	Locking on energisation and unlocking on de-energisation of solenoid
Product certifications	CSA UL
Standards	CSA C22.2 No 14 EN 1088/ISO 14119 IEC 60204-1 IEC 60947-5-1 ISO 12100 UL 508
Indivisible sale quantity	1

Complementary

Actuator forcible withdrawal rtc	500 N
Mechanical durability	1000000 cycles
Minimum actuation speed	0.01 m/s
Cable entry	1 entry tapped for 1/2" NPT
Electrical connection	Terminal, clamping capacity: 1 x 0.5...2 x 1.5 mm² with or without cable end

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Positive opening	With NC contact
Positive opening minimum force	15 N
Contacts type and composition	2 NC
Solenoid contacts type and composition	1 NC (slow-break)
Contact operation	Slow-break, simultaneous
Operating rate	10 cyc/mn for maximum durability
[Us] rated supply voltage	24 V - 20...10 %
Supply voltage type	AC/DC
Supply frequency	50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-5-1
[Ui] rated insulation voltage	300 V conforming to UL 508, 500 V conforming to IEC 60947-1, 300 V conforming to CSA C22.2 No 14
[Ie] rated operational current	0.55 A at 125 V, DC-13, Q300 conforming to IEC 60947-5-1, 0.27 A at 250 V, DC-13, Q300 conforming to IEC 60947-5-1, 3 A at 120 V, AC-15, B300 conforming to IEC 60947-5-1, 1.5 A at 240 V, AC-15, B300 conforming to IEC 60947-5-1
[Ithe] conventional enclosed thermal current	6 A
Power consumption in VA	10 VA
Electrical shock protection class	Class II conforming to IEC 61140
Short-circuit protection	10 A cartridge fuse type gG (gI)
Insulation	Double insulated
Width	110 mm
Depth	33 mm
Product weight	0.36 kg

Environment

IP degree of protection	IP67 conforming to EN/IEC 60529 and EN/IEC 60947-5-1
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C
Shock resistance	10 gn for 11 ms conforming to IEC 60068-2-27
Vibration resistance	5 gn (f= 10-500 Hz) conforming to IEC 60068-2-6
Protective treatment	TC

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months

Packing Units

Country of origin	FR (France)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916046784
Package 1 height	11 cm
Package 1 width	3.5 cm
Package 1 length	9.5 cm
Package 1 weight	0.5 kg
New Package 2 GTIN 14	13666916046781
New Package 3 GTIN 14	23666916046788