

Product data sheet

XE3NP2151

Limit switch contact block XE3NP, 1NC+2NO, slow action, break before make, self-lifting clamp

Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch contact block
Device short name	XE3N
ETIM classification	ETIM 9 - EC000041 - Auxiliary contact block
Number of poles	3
Product compatibility	XCKD XCKJ XCKL XCKM XCKP XCKS
Indivisible sale quantity	1

Complementary

Minimum actuation speed	6 m/mn
Contact code designation	B300, AC-15 (Ue = 240 V), Ie = 1.5 A, Ithe = 6 A conforming to IEC 60947-5-1 appendix A, R300, DC-13 (Ue = 250 V), Ie = 0.1 A conforming to IEC 60947-5-1 appendix A
Electrical durability	5000000 cycles, DC-13 120 V, 2 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C, 5000000 cycles, DC-13 24 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C, 5000000 cycles, DC-13 48 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 0.75 mm²
Positive opening	With
Contacts insulation form	Zb
Contacts type and composition	2 NO + 1 NC
Contacts material	Silver plated contacts
Contact operation	Slow-break, break before make
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60664, 4 kV conforming to IEC 60947-1
[Ui] rated insulation voltage	300 V conforming to UL 508, 300 V conforming to CSA C22.2 No 14, 400 V (pollution degree 3) conforming to IEC 60947-1
Resistance across terminals	25 mOhm conforming to IEC 60255-7 category 3
Short-circuit protection	6 A cartridge fuse, type gG

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months

Packing Units

Country of origin	FR (France)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916091289
Package 1 height	11 cm
Package 1 width	2.5 cm
Package 1 length	7.5 cm
Package 1 weight	0.021 kg
Unit type of package 2	CAR
Number of units in package 2	1
New Package 2 GTIN 14	13666916091286
Package 2 height	11 cm
Package 2 width	7.5 cm
Package 2 length	2.5 cm
Package 2 weight	0.021 kg
New Package 3 GTIN 14	23666916091283