

Product data sheet

XGHB441645

RFID electronic tag XG, 13.56 MHz, flat form 40x40x15, 16 kBytes, FRAM

Main

Range of product	Telemecanique Radio frequency identification XG
Product or component type	Electronic tag
RFID electronic tag name	XGHB
Design	Flat form 40 x 40 x 15
Sensor design	Flat form 40 x 40 x 15
ETIM classification	ETIM 9 - EC002996 - RFID transponder
Material	PBT (polybutylene terephthalate)
Fixing mode	By clips by screws
RFID frequency	13.56 MHz
[Sn] nominal sensing distance	25 mm with XGCS49, 39 mm with XGCS89
Memory capacity	16 kB
Outer dimension	40 x 40 x 15 mm
Read time	6 + 0.25 x (number of 16-bit words) ms
Write time	6 + 0.25 x (number of 16-bit words) ms
Standards	ISO 14443
Indivisible sale quantity	1
Quantity per set	Set of 1

Complementary

Memory type	FeRAM
Number of read cycles	10000000000
Data retention time	10 year
Memory operation	Read/write
Number of write cycles	10000000000 at -25-70 °C
Mounting location	Possible on metal support
Passing speed of object	2.3 m/s with XGCS49 (read a serial number), 1.8 m/s with XGCS49 (read a word), 1.7 m/s with XGCS49 (read or write 10 words), 3.8 m/s with XGCS89 (read a serial number), 3 m/s with XGCS89 (read a word), 2.6 m/s with XGCS89 (read or write 10 words), 3.8 m/s with XGCS85 (read a serial number), 3 m/s with XGCS85 (read a word), 2.6 m/s with XGCS85 (read or write 10 words)
Product weight	0.031 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IK degree of protection	IK02 conforming to IEC 62262
IP degree of protection	IP68
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for operation	-25-70 °C
Ambient air temperature for storage	-40…85 °C
Shock resistance	30 gn conforming to IEC 60068-2-27 for 11 ms
Vibration resistance	2 mm conforming to IEC 60068-2-6 (f = 5-29.5 Hz), 7 gn conforming to IEC 60068-2-6 (f = 29.5-150 Hz)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months


Packing Units

Country of origin	FR (France)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916060568
Package 1 height	2 cm
Package 1 width	6.1 cm
Package 1 length	8.8 cm
Package 1 weight	0.031 kg
Unit type of package 2	S01
Number of units in package 2	32
New Package 2 GTIN 14	13666916060565
Package 2 height	15 cm
Package 2 width	15 cm
Package 2 length	40 cm
Package 2 weight	1.729 kg
New Package 3 GTIN 14	23666916060562

Technical Drawings

Dimensions


Updatable Code Electronic Tags




- (1) For CHC type screws

Minimum Mounting Distances

Distance Between Tags



Minimum Mounting Distances in a Metal Structure



- (e) ≥ 20 mm.