

Product data sheet

XSAV11801L05

Inductive rotation sensor, XSAV, M30, Sn 10 mm, cable 5 m, 6...150 c/min, 24...240 VAC/DC, rotation monitoring

Main

Range of product	Telemecanique Inductive proximity sensors XS
Series name	Application
Sensor name	XSA
Sensor type	Inductive proximity sensor
Product or component type	Sensor
Sensor design	Cylindrical M30
Device application	Rotation monitoring
ETIM classification	ETIM 9 - EC002714 - Inductive proximity switch
Body type	Fixed
Material	Metal
Front material	PPS
Enclosure material	Nickel plated brass
[Sn] nominal sensing distance	10 mm
Wiring technique	2-wire
Detector flush mounting acceptance	Flush mountable
Thread type	M30 x 1.5
Product certifications	CCC CSA UL
Marking	CE
Indivisible sale quantity	1

Complementary

Sensing range	8...15 mm
Repeat accuracy	<= 3% of Sr
Electrical connection	Cable
Cable length	5 m
Cable composition	2 x 0.34 mm²
Wire insulation material	PVC
Supply voltage limits	20-264 V AC/DC

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[Us] rated supply voltage	24...210 V DC, 24...240 V AC 50/60 Hz
Switching capacity in mA	5...200 mA DC, 5...350 mA AC
Voltage drop	<5.7 V (closed)
Status LED	Output state: 1 LED (red)
Output circuit type	AC/DC
Type of output signal	Discrete
Detection face	Frontal
Discrete output function	1 NC
Switching frequency	<= 100 Hz
Differential travel	3...15% of Fr
Residual current	1.5 mA open state
Threaded length	67 mm
Run-up delay at power-up	9 s standard
Length	81 mm
Size	81 mm
Product weight	0.3 kg

Environment

IP degree of protection	IP67 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Warranty

Warranty	18 months


Packing Units

Country of origin	FR (France)
Unit type of package 1	PCE
Number of units in package 1	1
New Package 1 GTIN-13	3666916009208
Package 1 height	6.6 cm
Package 1 width	9.5 cm
Package 1 length	13 cm
Package 1 weight	0.35 kg

Unit type of package 2	S02
Number of units in package 2	14
New Package 2 GTIN 14	13666916009205
Package 2 height	15 cm
Package 2 width	30 cm
Package 2 length	40 cm
Package 2 weight	5.355 kg
Unit type of package 3	CAR
Number of units in package 3	1
New Package 3 GTIN 14	23666916009202
Package 3 height	13 cm
Package 3 width	6.6 cm
Package 3 length	9.5 cm
Package 3 weight	0.35 kg


Technical Drawings

Dimensions




(1)

Minimum Mounting Distances



Side by side
e (1) ≥
Face to face
e (2) ≥
Facing a metal object
e (3) ≥


Wiring Schemes



2-wire AC or DC
BU :
BN :

Performance Curves

Standard Steel Target : 30x30x1 mm



(1)
(2)
(y)