

# Product data sheet

# XUB6BPXWL2

Photoelectric sensor XUB, metal, diffuse, Sn 0.5 m, cable 2 m, PNP, NO/NC

## Main

| | |
|---|---|
| Range of product | Telemecanique Photoelectric sensors XU |
| Series name | General purpose single mode |
| Sensor name | XUB |
| Electronic sensor type | Photo-electric sensor |
| Sensor design | Cylindrical M18 |
| ETIM classification | ETIM 9 - EC001821 - Diffuse reflective photoelectric sensor |
| Material | Metal |
| Lens material | PMMA |
| Enclosure material | PC/PBT |
| [Sn] nominal sensing distance | 0.35-0.35 m diffuse |
| Maximum sensing distance | 0.5 m diffuse |
| Wiring technique | 4 wires |
| Diameter | 18 mm |
| Detection system | Diffuse |
| Line of sight type | 90° lateral |
| Delay response | 0.5 ms |
| Indivisible sale quantity | 1 |

## Complementary

| | |
|---|---|
| Sensing range | 0.01...0.5 m |
| Electrical connection | Cable |
| Cable length | 2 m |
| Supply voltage limits | 10-30 V DC |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection |
| Supply circuit type | DC |
| Switching capacity in mA | <= 100 mA (overload and short-circuit protection) |
| Maximum voltage drop | <2 V (closed state)no-load |
| Current consumption | < 20 mA no load |
| Emission | Red LED diffuse |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| Setting-up | Sensitivity by potentiometer |
| Output type | Discrete |
| Type of output signal | Discrete |
| Discrete output type | PNP |
| Discrete output function | 1 NO or 1 NC programmable |
| Switching frequency | 1000 Hz |
| Status LED | 1 LED (green) for supply on/stability, 1 LED (orange) for output state |
| Delay first up | 100 ms |
| Delay recovery | 0.5 ms |
| Length | 55.2 mm |
| Product weight | 0.09 kg |

## Environment

| | |
|---|---|
| IP degree of protection | IP67 conforming to IEC 60529, IP65 conforming to IEC 60529 |
| Ambient air temperature for operation | -30…55 °C |
| Ambient air temperature for operation | -30-55 °C |
| Ambient air temperature for storage | -40…70 °C |
| Shock resistance | 30 gn (duration = 11 ms) for for every axis conforming to IEC 60068-2-27 |
| Vibration resistance | 7 gn, amplitude = +/- 1.5 mm (f = 10-55 Hz)for every axis conforming to IEC 60068-2-6 |
| Relative humidity | 35-95 % |
| Immunity to ambient light | 40000 lux sunlight, 10000 lux incandescent light |

## Offer Sustainability

| | |
|---|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. Fo more information go to www.P65Warnings.ca.gov |

## Warranty

| | |
|---|---|
| Warranty | 18 months |

## Packing Units

| | |
|---|---|
| Country of origin | ID (Indonesia) |
| Unit type of package 1 | PCE |
| Number of units in package 1 | 1 |
| New Package 1 GTIN-13 | 3666916035085 |
| Package 1 height | 1.8 cm |
| Package 1 width | 1.6 cm |
| Package 1 length | 4.4 cm |
| Package 1 weight | 0.095 kg |

| | |
|---|---|
| Unit type of package 2 | S02 |
| Number of units in package 2 | 36 |
| New Package 2 GTIN 14 | 13666916035082 |
| Package 2 height | 15 cm |
| Package 2 width | 30 cm |
| Package 2 length | 40 cm |
| Package 2 weight | 4.42 kg |
| Unit type of package 3 | P06 |
| Number of units in package 3 | 576 |
| New Package 3 GTIN 14 | 23666916035089 |
| Package 3 height | 70 cm |
| Package 3 width | 60 cm |
| Package 3 length | 80 cm |
| Package 3 weight | 68.26 kg |